

PORTMAX PM 93 PLUS - Specifiche tecniche



Description

PORTMAX PM 93 PLUS è stato particolarmente progettato per straddle carrier (gru a cavaliere) nelle operazioni portuali di movimentazione dei container. Lo pneumatico radiale All Steel con cinture in acciaio multistrato garantisce maggiore stabilità e durabilità. La speciale miscela antistatica del battistrada assicura eccellente resistenza al calore nonché una vita più lunga dello pneumatico. PORTMAX PM 93 PLUS offre una resistenza ridotta al rotolamento che migliora il risparmio di carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Straddle carrier

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

Dimensions US Standard

Usa code	94047680
Overall Width (inch)	16.7
Overall Diameter (inch)	59.6
Static Loaded Radius (inch)	27.5
Rolling Circumference (inch)	180.4
Rim Rec	11.25/2.0
Star Rating	**

Load capacity (lbs)

mph / psi	145
15	30900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 09:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..