

POWER RIB F2 - Scheda tecnica



Description

POWER RIB F2 è stato particolarmente sviluppato per trattori 2WD/2RM nelle applicazioni di lavorazione del terreno. Questo pneumatico per l'impiego principale sul campo è molto idoneo per tutte le operazioni che richiedono un eccellente controllo di sterzata.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricoltura: Trattore 2WD

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11L - 15 SL	STANDARD	94020430	F2	106 A8	8	8 LB	10 LB	11	32	14.7	95.4	TL	E11-106R-004652

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..