

POWER TRAX HD (FL) - Specifiche tecniche



Description

POWER TRAX HD è uno pneumatico a tele diagonali di alta qualità, appositamente progettato per carrelli elevatori in applicazioni industriali. Il battistrada profondo, la parete laterale extra spessa e il rivestimento resistente offrono una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali. Lo pneumatico presenta un'eccellente resistenza al taglio, al truciolo e allo strappo per superfici in cemento ruvide e dure. La protezione dei cerchioni, appositamente progettata, previene danni alla piana e alle ruote nell'area della flangia del cerchione.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	16
Section Width (mm)	270
Overall Diameter (mm)	1050
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005554

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	6175
25 STEER WHEEL	4750
10 OTHER VEHICLES	6175
25 OTHER VEHICLES	4750
STATIC SIDE LOADER	7150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..