

POWER TRAX HD - Specifiche tecniche



Description

Lo pneumatico premium POWER TRAX HD è appositamente progettato per le attrezzature in applicazioni portuali e sotterranee. Il battistrada profondo, la parete laterale extra spessa e il rivestimento resistente offrono una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali. Lo pneumatico presenta un'eccellente resistenza al taglio e ai trucioli, ed è particolarmente adatto per superfici ruvide e dure. La protezione dei cerchioni, appositamente progettata, previene danni alla piana e alle ruote nell'area della flangia del cerchione.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container
OTR: Veicolo per miniere sotterranee

Version	IMPLEMENT
Type	TT
Tyre Size	12.00 - 20
LI/SS	172 A8

Dimensions US Standard

Usa code	94055944
Ply Rating	20
Section Width (inch)	12.6
Overall Diameter (inch)	45.3
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-003422
Tread Depth	43

Load capacity (lbs)

mph / psi	145
25	13900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..