

RIB 774 (A) - Specifiche tecniche



Description

RIB 774 (A) è uno pneumatico a sezione bassa per attrezzi agricoli, che offre elevata capacità di carico insieme ad un lungo ciclo di vita del prodotto. Lo pneumatico è ideale per l'agricoltura moderna ed è idoneo per applicazioni di raccolta del fieno e di trasporto con presse per balle di fieno e rimorchi.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Rimorchio

Version	STANDARD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	210
Overall Diameter (mm)	610
Static Loaded Radius (mm)	288
Rolling Circumference (mm)	1888
Rim Rec	AG 6.75
ECE	E11-106R-003608

Load capacity (Kg)

km/h / bar	7.00
10 FR	1610
25 FR	1370
30 FR	1290
40 FR	1150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..