

RIB 774 (C) - Specifiche tecniche



Description

RIB 774 (C) è uno pneumatico a sezione bassa con base stretta (narrow) per attrezzi agricoli, ideale per l'agricoltura moderna. Lo pneumatico è idoneo per applicazioni di raccolta del fieno e di trasporto con presse per balle di fieno e rimorchi su strada e fuori strada. Lo pneumatico offre elevata capacità di carico e un lungo ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	19.0/45 - 17
LI/SS FREE ROLLING	138 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	455
Overall Diameter (mm)	845
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2518
Rim Rec	16.00
ECE	E11-106R-004589

Load capacity (Kg)

	km/h / bar	2.25
	10 FR	3305
	25 FR	2810
	30 FR	2645
	40 FR	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 18:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..