

RIB F3 - Specifiche tecniche



Description

RIB F3 è uno pneumatico per l'impiego principale sul campo con trattori 2WD nelle applicazioni per la lavorazione del terreno e di trasporto. Alcune misure sono idonee per applicazioni di trasporto con attrezzi agricoli e rimorchi. RIB F3 è lo pneumatico ideale per tutte le operazioni che richiedono un elevato livello di manipolazioni e manovre. È stato sviluppato con una mescola dura che assicura durabilità superiore e resistenza alle stoppie.

UM

US Standard

Construction

❖ BIAS

Machinery

Agricoltura: Trattore 2WD • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions US Standard

Usa code	94060016
Ply Rating	12
Section Width (inch)	9.6
Overall Diameter (inch)	34.6
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	101.3
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004592
TRA Code	F3

Load capacity (lbs)

mph / psi	68
20	3090
25	2470

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..