

RIDEMAX FL 615 - Scheda tecnica



Description

RIDEMAX FL 615 è uno pneumatico radiale flotation adatto alle ruote non motrici di rimorchi agricoli, autocisterne e spargitori. La struttura con cinture in acciaio offre un'elevata resistenza alla perforazione, una maggiore durabilità e un'alta capacità di carico. RIDEMAX FL 615 assicura una bassa resistenza al rotolamento durante il trasporto su strada ed eccezionali proprietà di autopulitura in campo. La spalla arrotondata e l'ampia area di impronta a terra garantiscono la protezione del suolo.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Spargitore • Autobotte • Rimorchio

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
800/65 R 32	STEEL BELTED	185 D	185 D	185 D	DW 27 B		830	1853	834	5624	875	TL	E11-106R-007528
VF800/65 R 32	STEEL BELTED	190 D	190 D	190 D	DW 28 B		815	1850	811	5610	875	TL	E11-106R-0010408

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 04:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..