

RIDEMAX FL 690 - Scheda tecnica



Description

RIDEMAX FL 690 è uno pneumatico radiale Flotation e di trasporto idoneo per rimorchi e autobotti. È uno pneumatico idoneo per applicazioni 75% su strada. Per rispondere alla domanda di carichi sempre più pesanti nell'agricoltura moderna, BKT ha sviluppato questo pneumatico con cinture in acciaio per renderlo forte e supportare carichi molto pesanti, incrementando la produttività dell'agricoltore. La bassa resistenza al rotolamento contribuisce ad un notevole risparmio di carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio
Industriale: Rimorchio

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
28L R 26 (750/65 R 26)	STANDARD	94034321	176 A8/173 B	DW 25 B	DW 23 B	28.3	62.6	27.4	186.8	TL	E11-106R-002985
30.5L R 32	STANDARD	94033836	184 A8/181 B	DH 27 B	DW 27 B	31.1	70.9	31.7	213.8	TL	E11-106R-002986
800/60 R 32	STANDARD	94066254	185D	DH 27 B	DW 27 B	31.5	70.9	32.2	214.7	TL	E11-106R-006480
VF 900/65 R 32 (VF35.5LR32)	STANDARD	94067176	197 D	DW 31 B	DW 30 ; TW 30	36.6	78.2	33	231.4	TL	E11-106R-006917

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..