

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	560/55 R 22.5
LI/SS	162 D

Dimensions International Standard

Section Width (mm)	543
Overall Diameter (mm)	1180
Static Loaded Radius (mm)	533
Rolling Circumference (mm)	3614
SRI (mm)	550
Rim Rec	AG 16.00
Rim Alt	17.00 ; 20.00
ECE	E11-106R-006972

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
70	1645	1990	2205	2555	2900	3200	3505	3850	4110	4325
65	1805	2185	2425	2805	3185	3515	3850	4230	4515	5750
50	2185	2645	2935	3395	3855	4255	4660	5120	5465	5750
40	2455	2975	3295	3815	4330	4785	5235	5750	6140	6460
25	2855	3455	3830	4430	5030	5555	6080	6680	7130	7505
10	3250	3935	4365	5045	5730	6330	6930	7610	8125	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 16:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..