

RIDEMAX IT 696 - Specifiche tecniche



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

US Standard

Construction



RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	300/80 R 24 IND (11.2 R 24)
LI/SS	133 A8/128 D

Dimensions US Standard

Usa code	94033881
Section Width (inch)	11.6
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	129.8
Rim Rec	DW 10
ECE	E4-106R-002292

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	1860	2300	2700	3130	3530	3970
30	2010	2480	2910	3380	3800	4280
25	2140	2630	3090	3580	4050	4540
20	2230	2740	3220	3750	4220	4740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 05:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..