

RIDEMAX IT 696 - Specifiche tecniche



Description

RIDEMAX IT 696 è caratterizzato da un disegno unico del battistrada e un'ampia impronta che fornisce eccellente grip per applicazioni su strada anche in condizioni invernali. Lo pneumatico è molto idoneo per applicazioni di trasporto e nell'ambito municipalità/manutenzione grazie alle caratteristiche dell'alta velocità e alla carcassa robusta. Il disegno del battistrada è stato particolarmente sviluppato per i servizi pesanti e garantisce una bassa resistenza al rotolamento che si traduce in risparmio di carburante e grande stabilità.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TL
Tyre Size	340/80 R 18 IND
LI/SS	143 A8/138 D

Dimensions International Standard

Section Width (mm)	343
Overall Diameter (mm)	1001
Static Loaded Radius (mm)	458
Rolling Circumference (mm)	2980
SRI (mm)	475
Rim Rec	11 ; 11 SDC ; W 11
Rim Alt	W 10 ; 12 ; 12 SDC
ECE	E11-106R-002987

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.5	4.0
65	920	1135	1345	1535	1745	1960	2100	2360
50	995	1225	1455	1660	1885	2115	2270	2550
40	1065	1310	1555	1770	2015	2260	2425	2725
30	1110	1365	1620	1845	2100	2355	2525	2835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 14:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..