

ROCK GRIP E4 - Specifiche tecniche



Description

ROCK GRIP (E-4) è uno pneumatico a tele incrociate specificamente progettato per dumper rigidi impiegati nelle operazioni di miniera o di cava. Ogniqualvolta le vostre condizioni operative per i trasporti brevi sul sito richiedano sia resistenza al calore che protezione dai tagli, ROCK GRIP è il giusto pneumatico su cui fare affidamento.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dumper rigido

Version	STANDARD
Type	TT
Tyre Size	18.00 - 33

Dimensions US Standard

Usa code	94015535
Ply Rating	36
Overall Width (inch)	20.1
Overall Diameter (inch)	74.3
Static Loaded Radius (inch)	34.2
Rolling Circumference (inch)	219.9
Rim Rec	13.00/2.5
TRA Code	E4
Tread Depth	75

Load capacity (lbs)

mph / psi	94	123
30	24700	-
5	-	40800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..