

ROCK GRIP L4 - Scheda tecnica



Description

ROCK GRIP (L-4) è uno pneumatico a tele incrociate per pale gommate in operazioni di carico ardue su terreni insidiosi. La speciale mescola del battistrada è particolarmente resistente ad ogni tipo di tagli riducendo il rischio di foratura e quindi il tempo di fermo macchina. La profondità (L-4) del battistrada garantisce un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriale: Dozer • Pala caricatrice

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	24	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TT
14.00 - 25	STANDARD	L4	28	10.00/1.5		375	1410	649	4173	TL
14.00 - 25	STANDARD	L4	32	10.00/1.5		375	1410	649	4173	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 09:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..