

RT 851 - Scheda tecnica



Description

RT 851 è uno pneumatico R-1 particolarmente progettato per trattori nelle applicazioni con manti erbosi. Lo speciale disegno arrotondato dei ramponi è stato sviluppato per ridurre qualsiasi danno al manto erboso e alle piante in crescita, contenendo la compattazione del suolo. La robusta carcassa in nylon con le cinture forti in poliestere garantiscono trazione straordinaria oltre a maggiore capacità di carico.

UM

International Standard

Construction



RADIAL

Machinery

Agricoltura: Trattore

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
14.9L R 20 (375/75 R 20)	STANDARD	R1	119 A8/B	W 13	W 11; W 12; W 14	378	1100	498	3286	525	TL	E11-106R-002989

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 12:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..