

SAND STAR - Specifiche tecniche



Description

SAND STAR è uno pneumatico con disegno del battistrada a blocchi, particolarmente sviluppato per rimorchi. Assicura eccellente trazione su superfici sabbiose ed ottimo contatto con il terreno, riducendo anche la compattazione del suolo.

UM

International Standard

Construction

BIAS

Machinery

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	9.00 - 13
LI/SS	108 D

Dimensions International Standard

Ply Rating	6
Section Width (mm)	245
Overall Diameter (mm)	784
Rim Rec	5.50 F
Rim Alt	5.50 WB
ECE	E11-106R-005296

Load capacity (Kg)

km/h / bar	3.10
65	1000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 13/05/2025 23:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..