

SIERRA MAX - Specifiche tecniche



Description

SIERRA MAX è lo pneumatico BKT per applicazioni ATV e giardinaggio. Grazie alla sua costruzione radiale, lo pneumatico offre una guida notevolmente più morbida e più confortevole anche su terreni estremi come il deserto o superfici terrose e rocciose. Il particolare disegno del battistrada e la sua impronta più larga conferiscono una trazione anteriore e laterale senza eguali.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 26 X 9 R 14
LI/SS	48 N

Dimensions International Standard

Section Width (mm)	230
Overall Diameter (mm)	675
Static Loaded Radius (mm)	307
Rolling Circumference (mm)	2005
Rim Rec	7.00
Star Rating	***
ECE	E11-75R-005095

Load capacity (Kg)

km/h / bar	0.50
140	180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 23:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..