

SIERRA MAX - Specifiche tecniche



Description

SIERRA MAX è lo pneumatico BKT per applicazioni ATV e giardinaggio. Grazie alla sua costruzione radiale, lo pneumatico offre una guida notevolmente più morbida e più confortevole anche su terreni estremi come il deserto o superfici terrose e rocciose. Il particolare disegno del battistrada e la sua impronta più larga conferiscono una trazione anteriore e laterale senza eguali.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo ATV

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94052622
Section Width (inch)	11
Overall Diameter (inch)	27.6
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	82.3
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005097

Load capacity (lbs)

mph / psi	7
87	495

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 10:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..