

SKID POWER PLUS - Specifiche tecniche



Description

SKID POWER PLUS è stato sviluppato per pale skid steer nel settore costruzioni. I tasselli più larghi garantiscono eccellente trazione nonché ottime proprietà di autopulitura. Lo pneumatico si distingue per il battistrada extra profondo insieme alla maggiore protezione dei fianchi, assicurando eccellente resistenza a tagli e strappi oltre a straordinaria durabilità. SKID POWER PLUS è lo pneumatico ideale per superfici terrose. La larga area di contatto assicura ottima stabilità durante le operazioni.

UM

US Standard

Construction

✚ BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	10 - 16.5

Dimensions US Standard

Usa code	94054664
Ply Rating	8
Section Width (inch)	9.9
Overall Diameter (inch)	30.5
Rim Rec	8.25

Load capacity (lbs)

mph / psi	60
5	4140
10	3270
15	3020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/04/2025 10:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..