

## SR 713 - Specifiche tecniche



### Description

SR 713 è uno pneumatico radiale **All Steel** con tecnologia VF per attrezzi agricoli. Lo pneumatico è caratterizzato da una robusta carcassa con cinture in acciaio multistrato e da un battistrada con disegno a scanalature multiple che garantiscono una bassa resistenza al rotolamento oltre all'usura uniforme del battistrada. Grazie ad un'impronta larga, questo pneumatico VF assicura una ridotta compattazione del suolo. SR 713 si distingue sia in termini di prestazioni che per la sua affidabilità, offrendo ottimi livelli di velocità anche su strada.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agricoltura: Attrezzi agricoli

|           |                  |
|-----------|------------------|
| Version   | STANDARD         |
| Type      | TL               |
| Tyre Size | VF 295/75 R 22.5 |
| LI/SS     | 151 D            |

Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94057832        |
| Overall Width (inch)         | 11              |
| Overall Diameter (inch)      | 40.2            |
| Static Loaded Radius (inch)  | 17.7            |
| Rolling Circumference (inch) | 119.8           |
| Rim Rec                      | 9.00            |
| Rim Alt                      | 8.25            |
| ECE                          | E11-106R-005500 |
| TRA Code                     | I1              |

Load capacity (lbs)

| mph/psi | 35    | 38    | 41    | 44    | 46    | 49    | 52    | 55    | 58    | 61    | 64    |
|---------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 0       | 10765 | 11360 | 12330 | 13065 | 13430 | 13800 | 14720 | 15180 | 15985 | 17020 | 17480 |
| 5       | 8425  | 8890  | 9650  | 10225 | 10510 | 10800 | 11520 | 11880 | 12510 | 13320 | 13680 |
| 10      | 8095  | 8545  | 9275  | 9825  | 10105 | 10380 | 11070 | 11420 | 12025 | 12800 | 13150 |
| 15      | 7395  | 7805  | 8470  | 8975  | 9225  | 9480  | 10110 | 10430 | 10980 | 11690 | 12010 |
| 20      | 7065  | 7460  | 8095  | 8575  | 8820  | 9060  | 9665  | 9965  | 10495 | 11175 | 11475 |
| 25      | 6365  | 6720  | 7290  | 7725  | 7940  | 8160  | 8705  | 8975  | 9450  | 10065 | 10335 |
| 30      | 5665  | 5975  | 6485  | 6875  | 7065  | 7260  | 7745  | 7985  | 8410  | 8955  | 9195  |
| 35      | 5010  | 5285  | 5735  | 6080  | 6250  | 6420  | 6850  | 7060  | 7435  | 7920  | 8130  |
| 40      | 4680  | 4940  | 5360  | 5680  | 5840  | 6000  | 6400  | 6600  | 6950  | 7400  | 7600  |
| 43      | 4260  | 4495  | 4880  | 5170  | 5315  | 5460  | 5825  | 6005  | 6325  | 6735  | 6915  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 13:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..