

TR 133 - Specifiche tecniche



Description

TR 133 è stato specialmente progettato per trattori nelle applicazioni di lavorazione della terra. Grazie al numero maggiore di ramponi, lo pneumatico si distingue per l'eccellente trazione e lo straordinario comfort nonché le proprietà di autopulitura avanzate. TR 133 garantisce un ciclo di vita prolungato dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38 (14.00 - 38)
LI/SS	132 A8

Dimensions US Standard

Usa code	94043897
Ply Rating	10
Section Width (inch)	13.8
Overall Diameter (inch)	62.2
Static Loaded Radius (inch)	28.9
Rolling Circumference (inch)	190.7
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003549
TRA Code	R1

Load capacity (lbs)

mph / psi	36
25	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..