

TR 135 - Specifiche tecniche



Description

TR 135 è molto idoneo per trattori nelle applicazioni di lavorazione del suolo. La carcassa rinforzata e la speciale miscela resistente a tagli e lacerazioni assicurano un ciclo di vita prolungato dello pneumatico. Ottime performance in tema di trazione, proprietà di autopulitura e capacità di carico sono le caratteristiche chiave che rendono TR 135 lo pneumatico ideale anche sulle condizioni più difficili del terreno.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	9.5 - 20
LI/SS	107 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	240
Overall Diameter (mm)	955
Static Loaded Radius (mm)	454
Rolling Circumference (mm)	2888
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-002642
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.80
30	975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 11:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..