

TR 138 - Scheda tecnica



Description

TR 138 è stato specificamente sviluppato per sollevatori telescopici e terne nell'agricoltura ed è particolarmente idoneo per la lavorazione del terreno e applicazioni di irrorazione. Ottima trazione su terreno morbido, autopulitura e stabilità sono le caratteristiche chiave che rendono TR 138 lo pneumatico ideale anche in condizioni difficili del terreno.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Terna • Sollevatore telescopico

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
17.5L - 24	STANDARD	94061877	151 A8	12	DW 15L	DW 14L	17.7	50.8	22.7	151	TL	E11-106R-005232

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 02:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..