

TR 270 - Specifiche tecniche



Description

TR 270 è uno pneumatico per trattori idoneo per applicazioni di lavorazione della terra. Lo pneumatico è stato specialmente progettato per offrire massime prestazioni su terreni umidi e bagnati. In queste condizioni del suolo, ad uno pneumatico è richiesto di offrire grip superiore insieme a proprietà avanzate di autopulitura. TR 270 soddisfa perfettamente queste caratteristiche.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	13.6 - 38
LI/SS	119 A8

Dimensions US Standard

Usa code	94051069
Ply Rating	6
Section Width (inch)	13.6
Overall Diameter (inch)	63
Rolling Circumference (inch)	190.1
Rim Rec	W12
Rim Alt	DW12A , W11
ECE	E11-106R-004340
TRA Code	R2

Load capacity (lbs)

mph / psi	22
25	3300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 02:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..