

## TR 273 - Scheda tecnica



### Description

TR 273 è uno pneumatico per trattori idoneo per le applicazioni di lavorazione della terra. Lo pneumatico è stato specialmente progettato per offrire massime prestazioni su terreni umidi e bagnati. In queste condizioni del suolo, ad uno pneumatico è richiesto di offrire grip superiore insieme a proprietà avanzate di autopulitura. TR 273 soddisfa perfettamente queste caratteristiche.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

| SIZE      | Version  | TRA Code | LI/SS  | PR | RIM REC           | RIM ALT         | SW  | OD   | SLR | RC   | Type | TKPH | ECE             |
|-----------|----------|----------|--------|----|-------------------|-----------------|-----|------|-----|------|------|------|-----------------|
| 12.4 - 24 | STANDARD | R2       | 121 A6 | 8  | W 11              | W 10            | 315 | 1195 | 550 | 3722 | TT   | 0    | E11-106R-004100 |
| 13.6 - 24 | STANDARD | R2       | 123 A6 | 8  | W 12              | W 11            | 350 | 1240 | 570 | 3795 | TT   | 1    | E11-106R-005252 |
| 14.9 - 24 | STANDARD | R2       | 128 A6 | 8  | W 13              | W 12            | 380 | 1310 | 595 | 4044 | TT   |      | E11-106R-004514 |
| 14.9 - 24 | STANDARD | R2       | 132 A6 | 10 | W 13              | W 12            | 380 | 1310 | 595 | 4044 | TT   |      | E11-106R-004515 |
| 18.4 - 26 | STANDARD | R2       | 146 A6 | 12 | W 16              | W 15            | 470 | 1490 | 673 | 4534 | TT   | 1    | E11-106R-005314 |
| 23.1 - 26 | STANDARD | R2       | 156 A6 | 14 | DW 20 A ; DW 20 B |                 | 590 | 1655 | 737 | 5053 | TT   |      | E11-106R-004628 |
| 23.1 - 26 | STANDARD | R2       | 149 A6 | 10 | DW 20 A ; DW 20 B |                 | 590 | 1655 | 737 | 5053 | TT   |      | E11-106R-003620 |
| 23.1 - 26 | STANDARD | R2       | 153 A6 | 12 | DW 20 A ; DW 20 B |                 | 590 | 1655 | 737 | 5053 | TT   |      | E11-106R-003395 |
| 14.9 - 28 | STANDARD | R2       | 130 A6 | 8  | W 13              | W 12            | 385 | 1410 | 651 | 4368 | TT   |      | E11-106R-004516 |
| 16.9 - 30 | STANDARD | R2       | 143 A6 | 12 | W 15 L            | W 14 L          | 435 | 1530 | 706 | 4800 | TT   | 1    | E11-106R-005315 |
| 18.4 - 30 | STANDARD | R2       | 149 A6 | 12 | W 16 L            | W 15 L          | 465 | 1585 | 723 | 4924 | TT   |      | E11-106R-003621 |
| 23.1 - 30 | STANDARD | R2       | 151 A6 | 10 | DW 20 A ; DW 20 B |                 | 590 | 1748 | 794 | 5356 | TT   |      | E11-106R-003622 |
| 23.1 - 30 | STANDARD | R2       | 157 A6 | 14 | DW 20 A ; DW 20 B |                 | 590 | 1748 | 794 | 5356 | TT   | 0    | E11-106R-003645 |
| 18.4 - 34 | STANDARD | R2       | 150 A6 | 12 | DW 16A            | W16L,W15L,DW15L | 475 | 1701 | 775 | 5253 | TT   |      | E11-106R-004517 |
| 23.1 - 34 | STANDARD | R2       | 153 A6 | 10 | DW 20 A ; DW 20 B |                 | 590 | 1850 | 833 | 5634 | TT   |      | E11-106R-003623 |
| 23.1 - 34 | STANDARD | R2       | 160 A6 | 14 | DW 20 A ; DW 20 B |                 | 590 | 1850 | 831 | 5674 | TT   | 1    | E11-106R-003646 |
| 18.4 - 38 | STANDARD | R2       | 152 A6 | 12 | W 16              | W 15            | 465 | 1800 | 822 | 5579 | TT   | 1    | E11-106R-005316 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 22:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..