

TR 319 - Specifiche tecniche



Description

TR 319 è uno pneumatico per attrezzi agricoli, macchine per il raccolto di frutteti e scavafossi nelle applicazioni in ambito municipalità nonché per la lavorazione della terra. Lo pneumatico mostra un'ampia area di contatto che si traduce in ottima trazione. Pertanto, TR 319 è molto idoneo per applicazioni su superficie bagnate che richiedono eccellenti doti di stabilità e autopulitura.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Macchina per il raccolto di frutteti • Scavafossi

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12
LI/SS	116 A3

Dimensions US Standard

Usa code	94043637
Ply Rating	8
Section Width (inch)	12.5
Overall Diameter (inch)	25.2
Static Loaded Radius (inch)	11.4
Rolling Circumference (inch)	75.1
Rim Rec	10.50 AT
Rim Alt	8.0 AT ; 8.5 AT ; 9.0 AT
ECE	E11-106R-003560

Load capacity (lbs)

mph / psi	44
10	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..