

TR 463 - Scheda tecnica



Description

TR 463 è stato specificamente sviluppato per terne e trattori industriali. Realizzato con una mescola superiore del battistrada insieme alla robusta carcassa in nylon, lo pneumatico garantisce i migliori risultati nelle applicazioni industriali e OTR nonché sui cantieri. TR 463 assicura un'eccellente trazione per le ruote motrici.

UM

International Standard

Construction

✚ BIAS

Machinery

Industriale: Terna • Trattore industriale

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
16.9 - 24	INDUSTRIAL	R4	149 A8	12	DW 15 L	DW 14 L	445	1300	584	3877		TL	
18.4 - 26	INDUSTRIAL	R4	156 A8	12	DW 16 L	DW 15 L	480	1425	637	4215	675	TL	
16.9 - 28	INDUSTRIAL	R4	152 A8	12	DW 15 L	DW 14 L	450	1405	636	4190		TL	E11-106R-003626

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 10:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..