

TR 882 - Specifiche tecniche



Description

TR 882 è uno pneumatico molto versatile per svariate applicazioni e macchine. Progettato per essere impiegato con attrezzi agricoli e macchine per la raccolta del fieno/pressapaglia nonché macchine per piantagioni della canna da zucchero. Progettato con una mescola speciale per ridurre i danni, questo pneumatico si distingue per durabilità e trazione eccellenti in qualsiasi condizione del campo. TR 882 è anche disponibile nelle versioni "aramid-belted", "HD" e "special" per soddisfare le esigenze più specifiche degli utilizzatori finali.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio
Industriale: Rimorchio

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	122 A8
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	400
Overall Diameter (mm)	875
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2605
SRI (mm)	410
Rim Rec	AG 13.00
ECE	E11-106R-004330

Load capacity (Kg)

km/h / bar	2.40
10 FR	2970
25 FR	2525
30 FR	2375
40 FR	2120
10 DW	2100
25 DW	1785
30 DW	1680
40 DW	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 07:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..