

TRAC FARM PLUS - Specifiche tecniche



Description

TRAC FARM PLUS è uno pneumatico posteriore per trattori particolarmente sviluppato per la lavorazione della terra e applicazioni di trasporto. Lo pneumatico si distingue per il battistrada più profondo con ramponi a doppio angolo al fine di assicurare sia trazione eccellente che una guida confortevole sulla strada. Lo speciale disegno del battistrada offre maggiore contatto per una migliore stabilità e ottime proprietà di autopulitura. TRAC FARM PLUS assicura un ciclo di vita prolungato dello pneumatico.

UM

US Standard

Construction

✚ BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	130 A8

Dimensions US Standard

Usa code	94057436
Ply Rating	12
Section Width (inch)	15.4
Overall Diameter (inch)	54.3
Static Loaded Radius (inch)	25.3
Rolling Circumference (inch)	164.5
Rim Rec	W 13
Rim Alt	W 12 ; W 11
ECE	E11-106R-006811
TRA Code	R1

Load capacity (lbs)

mph / psi	34
25	4680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 11:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..