

## TRAC FARM - Specifiche tecniche



### Description

TRAC FARM è uno pneumatico per operazioni di servizio pesante specificamente progettato per trattori nelle applicazioni per la lavorazione del terreno e di trasporto. Il battistrada profondo e la speciale mescola resistente a tagli e lacerazioni rendono questo pneumatico idoneo per le condizioni operative più difficili, garantendo il migliore rendimento sull'investimento durante l'intero ciclo di vita del prodotto. TRAC FARM è stato progettato con un numero maggiore di ramponi per garantire eccellente trazione e ottime proprietà di autopulitura.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 12.4 - 28 |
| LI/SS     | 124 A6    |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Ply Rating                 | 10              |
| Section Width (mm)         | 320             |
| Overall Diameter (mm)      | 1295            |
| Static Loaded Radius (mm)  | 602             |
| Rolling Circumference (mm) | 3890            |
| SRI (mm)                   | 600             |
| Rim Rec                    | W 11            |
| Rim Alt                    | W 9, W 10       |
| ECE                        | E11-106R-004524 |
| TRA Code                   | R1              |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.40 |
| 30         | 1600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 03:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..