

TRAC GRADER + - Specifiche tecniche



Description

TRAC GRADER + (G-2) è uno pneumatico a tele incrociate per motolivellatrici, che rappresenta una scelta eccellente per i clienti orientati al budget. La carcassa durevole è progettata per resistere nel tempo. Il disegno autopulente del battistrada mostra una proporzione rampone-spazio che fornisce la migliore trazione in tutte le condizioni. La versione special è realizzata con una miscela speciale, resistente a tagli e strappi.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motolivellatrice

Version	STANDARD
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94014606
Ply Rating	12
Overall Width (inch)	14.3
Overall Diameter (inch)	53.1
Static Loaded Radius (inch)	23.5
Rolling Circumference (inch)	157.1
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC
TRA Code	G2
Tread Depth	32

Load capacity (lbs)

mph / psi	36
25	6800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 00:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..