

TRAC GRADER + - Specifiche tecniche



Description

TRAC GRADER + (G-2) è uno pneumatico a tele incrociate per motolivellatrici, che rappresenta una scelta eccellente per i clienti orientati al budget. La carcassa durevole è progettata per resistere nel tempo. Il disegno autopulente del battistrada mostra una proporzione rampone-spazio che fornisce la migliore trazione in tutte le condizioni. La versione special è realizzata con una miscela speciale, resistente a tagli e strappi.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Motolivellatrice

Version	STANDARD
Type	TT
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	364
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	598
Rolling Circumference (mm)	3990
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00 VA SDC; 10.00 WA SDC
TRA Code	G2
Tread Depth	25

Load capacity (Kg)

km/h / bar	2.50
40	3075

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 03:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..