

TRAC MASTER - Specifiche tecniche



Description

TRAC MASTER è uno pneumatico per la lavorazione della terra e le applicazioni per prati e giardinaggio, idoneo per trattori piccoli e attrezzi agricoli. Il disegno del battistrada è stato sviluppato per garantire ottima protezione del campo nonché eccellenti proprietà di autopulitura e trazione superiore sul campo.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Trattorino

Version	STANDARD
Type	TL
Tyre Size	300/60 - 12

Dimensions US Standard

Usa code	94013166
Ply Rating	8
Section Width (inch)	12
Overall Diameter (inch)	25.4
Static Loaded Radius (inch)	11.2
Rolling Circumference (inch)	74.2
Rim Rec	10.5
Rim Alt	9.5
ECE	E11-106R-003597

Load capacity (lbs)

mph / psi	46
30	2270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..