

TRAC MASTER - Scheda tecnica



Description

TRAC MASTER è uno pneumatico per la lavorazione della terra e le applicazioni per prati e giardinaggio, idoneo per trattori piccoli e attrezzi agricoli. Il disegno del battistrada è stato sviluppato per garantire ottima protezione del campo nonché eccellenti proprietà di autopulitura e trazione superiore sul campo.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Trattorino

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
300/60 - 12	STANDARD		8	10.5	9.5	306	645	285	1885	TL	E11-106R-003597
31 X 15.50 - 15	STANDARD		6	13 LB		405	792	370	2372	TL	E4-106R-002209
31 X 15.50 - 15	STANDARD		8	13 LB		405	792	370	2372	TL	E4-106R-002208
33 X 15.50 - 15	STANDARD		6	13 LB		404	865	378	2526	TL	E4-106R-002329
33 X 15.50 - 15	STANDARD		8	13 LB		404	865	378	2526	TL	E4-106R-002330
380/50 - 15	STANDARD	116 B	8	13 LB		380	780	364	2229	TL	E11-106R-008808

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..