

V-FLEXA - Specifiche tecniche



Description

V-FLEXA è uno pneumatico radiale appositamente progettato per rimorchi agricoli. È un prodotto flotation di ultima generazione dotato della tecnologia VF, che consente il trasporto di carichi pesanti sia su campo che su strada con una pressione di gonfiaggio inferiore del 30% rispetto a quella di uno pneumatico standard delle stesse dimensioni. Ulteriori cinture in acciaio conferiscono maggiore resistenza alla carcassa contro aggressioni. V-FLEXA non solo supporta carichi pesanti in totale sicurezza, ma evita anche la compattazione del suolo grazie alla perfetta distribuzione del peso. Inoltre, V-FLEXA offre ottime proprietà di autopulitura, durabilità e bassa resistenza al rotolamento.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	VF 560/60 R 22.5
LI/SS	166 D

Dimensions US Standard

Usa code	94066629
Section Width (inch)	21.9
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	147.9
Rim Rec	AG 16.00
ECE	E11-106R-006763

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46
45	4580	5860	7030	8100	8620	9790	10640
40	5030	6430	7720	8890	9470	10760	11690
30	5890	7530	9040	10410	11090	12590	13680
25	6500	8300	9960	11470	12230	13880	15080
5	8250	10550	12660	14580	15440	17640	19170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..