

V-FLEXA - Specifiche tecniche



Description

V-FLEXA è uno pneumatico radiale appositamente progettato per rimorchi agricoli. È un prodotto flotation di ultima generazione dotato della tecnologia VF, che consente il trasporto di carichi pesanti sia su campo che su strada con una pressione di gonfiaggio inferiore del 30% rispetto a quella di uno pneumatico standard delle stesse dimensioni. Ulteriori cinture in acciaio conferiscono maggiore resistenza alla carcassa contro aggressioni. V-FLEXA non solo supporta carichi pesanti in totale sicurezza, ma evita anche la compattazione del suolo grazie alla perfetta distribuzione del peso. Inoltre, V-FLEXA offre ottime proprietà di autopulitura, durabilità e bassa resistenza al rotolamento.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	VF 600/55 R 26.5
LI/SS	167 D

Dimensions International Standard

Section Width (mm)	615
Overall Diameter (mm)	1342
Static Loaded Radius (mm)	580
Rolling Circumference (mm)	3986
SRI (mm)	650
Rim Rec	AG20.00
ECE	E11-106R-006017

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
70	2130	2725	3315	3765	4360	4955
65	2340	2995	3650	4140	4795	5450
50	2740	3505	4270	4845	5610	6375
40	3020	3865	4710	5340	6185	7030
10	3840	4910	5985	6790	7860	8935

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 14:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..