

V-FLEXA - Specifiche tecniche



Description

V-FLEXA è uno pneumatico radiale appositamente progettato per rimorchi agricoli. È un prodotto flotation di ultima generazione dotato della tecnologia VF, che consente il trasporto di carichi pesanti sia su campo che su strada con una pressione di gonfiaggio inferiore del 30% rispetto a quella di uno pneumatico standard delle stesse dimensioni. Ulteriori cinture in acciaio conferiscono maggiore resistenza alla carcassa contro aggressioni. V-FLEXA non solo supporta carichi pesanti in totale sicurezza, ma evita anche la compattazione del suolo grazie alla perfetta distribuzione del peso. Inoltre, V-FLEXA offre ottime proprietà di autopulitura, durabilità e bassa resistenza al rotolamento.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	VF 650/55 R 26.5
LI/SS	171 D

Dimensions International Standard

Section Width (mm)	644
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	591
Rolling Circumference (mm)	4100
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E11-106R-006399

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8
70	2405	3075	3745	4250	4920	5595
65	2640	3380	4120	4670	5410	6150
50	3090	3955	4820	5465	6330	7195
40	3405	4360	5310	6025	6975	7930
10	4335	5545	6755	7660	8870	10085

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 00:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..