

XL GRIP (E3) - Specifiche tecniche



Description

XL GRIP (E-3) è uno pneumatico a tele incrociate per dumper rigidi, progettato appositamente per minimizzare il rischio di tagli e perforazioni in condizioni che richiedono eccezionale trazione. Queste caratteristiche si traducono in una vita prolungata dello pneumatico.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Dumper rigido

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94043347
Ply Rating	16
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3
Tread Depth	40

Load capacity (lbs)

mph / psi	40	54
30	12300	-
5	-	22000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/04/2025 06:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..