

XL GRIP (G3) - Specifiche tecniche



Description

XL GRIP (G-3) è uno pneumatico a tele incrociate per motolivellatrici sviluppato per minimizzare il rischio di tagli e perforazioni nelle applicazioni pesanti di livellamento che richiedono straordinaria trazione.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motolivellatrice

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94061846
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	G3
Tread Depth	40

Load capacity (lbs)

mph / psi	102
25	22150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 06:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..