

XL GRIP (G3) - Scheda tecnica



Description

XL GRIP (G-3) è uno pneumatico a tele incrociate per motolivellatrici sviluppato per minimizzare il rischio di tagli e perforazioni nelle applicazioni pesanti di livellamento che richiedono straordinaria trazione.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Motolivellatrice

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	SRI	Type	Tread Depth
13.00 - 24	STANDARD	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	350	1295	601	3872		TL	30
13.00 - 24	STANDARD	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	350	1295	601	3872		TT	30
14.00 - 24	STANDARD	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	365	1345	617	4002		TL	30
14.00 - 24	STANDARD	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	365	1345	617	4002		TT	30
16.00 - 24 (-)	STANDARD	G3	16	10.00 VA SDC	-	432	1450	654	4289	-	TL	32
18.00 - 25	STANDARD	G3	32	13.00/2.5	15.00/2.5	510	1615	739	4780		TL	32
18.00 - 25	STANDARD	G3	40	13.00/2.5	15.00/2.5	510	1615	739	4780		TL	32

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 14:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..