

XL GRIP IND3 (RTG) - Specifiche tecniche



Description

XL GRIP (IND-3) è uno pneumatico a tele incrociate per gru RTG nelle applicazioni di impilatura e sollevamento. Lo pneumatico è caratterizzato da una carcassa robusta realizzata con una mescola appositamente formulata che assicura un ciclo di vita prolungato del prodotto.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Gru RTG

Version	INDUSTRIAL
Type	TL
Tyre Size	24.00 - 35

Dimensions US Standard

Usa code	94039562
Ply Rating	48
Overall Width (inch)	25.8
Overall Diameter (inch)	83.9
Static Loaded Radius (inch)	38.4
Rolling Circumference (inch)	248.1
Rim Rec	17.00/3.5
TRA Code	IND3

Load capacity (lbs)

mph / psi	145
5	93700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27/04/2025 11:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..