

XL GRIP (SCRAPER) - Specifiche tecniche



Description

XL GRIP (SCRAPER) è uno pneumatico di base larga non direzionale particolarmente idoneo per scraper su qualsiasi terreno. Lo pneumatico è caratterizzato da una carcassa robusta e da una miscela speciale che assicurano elevata resistenza a tagli e perforazioni nonché durabilità e trazione eccellenti anche durante operazioni di servizio pesante. Ulteriori vantaggi sono ottime proprietà di autopulitura e stabilità eccezionale.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Ruspa

Version	STANDARD
Type	TL
Tyre Size	33.25 - 29

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	862
Overall Diameter (mm)	2120
Rim Rec	27.00/3.5
Rim Alt	26.00/3.5
TRA Code	E3
Tread Depth	46

Load capacity (Kg)

km/h / bar	3.25	4.50
50	15000	-
10	-	23600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/04/2025 15:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..